

# Merit Laureate® Hydrophilic Guide Wires

5 guide wires per box.

May not be available  
for all OEM applications.

## MERIT LAUREATE STANDARD HYDROPHILIC GUIDE WIRES

Catalog Number	Description	Size	Length cm
<b>LWSTDA3580</b>	Standard Body/Angled Tip	0.035" (0.89mm)	80cm (31.5")
<b>LWSTDA3880</b>	Standard Body/Angled Tip	0.038" (0.97mm)	80cm (31.5")
<b>LWSTDA25150</b>	Standard Body/Angled Tip	0.025" (0.64mm)	150cm (59")
<b>LWSTDA25180</b>	Standard Body/Angled Tip	0.025" (0.64mm)	180cm (71")
<b>LWSTDA25260EX</b>	Standard Body Exchange/Angled Tip	0.025" (0.64mm)	260cm (102")
<b>LWSTDA35150</b>	Standard Body/Angled Tip	0.035" (0.89mm)	150cm (59")
<b>LWSTDA35180</b>	Standard Body/Angled Tip	0.035" (0.89mm)	180cm (71")
<b>LWSTDA35220</b>	Standard Body/Angled Tip	0.035" (0.89mm)	220cm (87")
<b>LWSTDA35260EX</b>	Standard Body Exchange/Angled Tip	0.035" (0.89mm)	260cm (102")
<b>LWSTDA38120</b>	Standard Body/Angled Tip	0.038" (0.97mm)	120cm (47")
<b>LWSTDA38180</b>	Standard Body/Angled Tip	0.038" (0.97mm)	180cm (71")
<b>LWSTDA38260EX</b>	Standard Body Exchange/Angled Tip	0.038" (0.97mm)	260cm (102")
<b>LWSTDS25150</b>	Standard Body/Straight Tip	0.025" (0.64mm)	150cm (59")
<b>LWSTDS25180</b>	Standard Body/Straight Tip	0.025" (0.64mm)	180cm (71")
<b>LWSTDS25260EX</b>	Standard Body Exchange/Straight Tip	0.025" (0.64mm)	260cm (102")
<b>LWSTDS35150</b>	Standard Body/Straight Tip	0.035" (0.89mm)	150cm (59")
<b>LWSTDS35180</b>	Standard Body/Straight Tip	0.035" (0.89mm)	180cm (71")
<b>LWSTDS35220</b>	Standard Body/Straight Tip	0.035" (0.89mm)	220cm (87")
<b>LWSTDS35260EX</b>	Standard Body Exchange/Straight Tip	0.035" (0.89mm)	260cm (102")
<b>LWSTDS38180</b>	Standard Body/Straight Tip	0.038" (0.97mm)	180cm (71")
<b>LWSTDS38260EX</b>	Standard Body Exchange/Straight Tip	0.038" (0.97mm)	260cm (102")
<b>LWSTFA3580</b>	Stiff Body/Angled Tip	0.035" (0.89mm)	80cm (31.5")
<b>LWSTFA3880</b>	Stiff Body/Angled Tip	0.038" (0.97mm)	80cm (31.5")
<b>LWSTFA35150</b>	Stiff Body/Angled Tip	0.035" (0.89mm)	150cm (59")
<b>LWSTFA35180</b>	Stiff Body/Angled Tip	0.035" (0.89mm)	180cm (71")
<b>LWSTFA35220</b>	Stiff Body/Angled Tip	0.035" (0.89mm)	220cm (87")
<b>LWSTFA35260EX</b>	Stiff Body Exchange/Angled Tip	0.035" (0.89mm)	260cm (102")
<b>LWSTFA38150</b>	Stiff Body/Angled Tip	0.038" (0.97mm)	150cm (59")
<b>LWSTFS35180</b>	Stiff Body/Straight Tip	0.035" (0.89mm)	180cm (71")
<b>LWSTFS35220</b>	Stiff Body/Straight Tip	0.035" (0.89mm)	220cm (87")
<b>LWSTFS35260EX</b>	Stiff Body Exchange/Straight Tip	0.035" (0.89mm)	260cm (102")
<b>LWSTFS38150</b>	Stiff Body/Straight Tip	0.038" (0.97mm)	150cm (59")
<b>LWSTFS38180</b>	Stiff Body/Straight Tip	0.038" (0.97mm)	180cm (71")
<b>LWSTDA1880</b>	Standard Body/Angled Tip	0.018" (0.46mm)	80cm (31.5")
<b>LWSTDA18150</b>	Standard Body/Angled Tip	0.018" (0.46mm)	150cm (59")
<b>LWSTDA18180</b>	Standard Body/Angled Tip	0.018" (0.46mm)	180cm (71")
<b>LWSTDA18260EX</b>	Standard Body Exchange/Angled Tip	0.018" (0.46mm)	260cm (102")
<b>LWSTDS18150</b>	Standard Body/Straight Tip	0.018" (0.46mm)	150cm (59")
<b>LWSTDS18180</b>	Standard Body/Straight Tip	0.018" (0.46mm)	180cm (71")
<b>LWSTDS18260EX</b>	Standard Body Exchange/Straight Tip	0.018" (0.46mm)	260cm (102")