

Straight Guide Wires

PTFE-Coated, Inqwire® Guide Wires

Catalog Number	Description	Size	Length cm	Core	Heparin Coated	# Per Box
6646-11	Moveable Core	0.035" (0.89mm)	145	M		
6676-A1	Standard	0.018" (0.46mm)	150	F		
6676-B3	Standard	0.018" (0.46mm)	180	F		
6676-C1	Standard	0.021" (0.53mm)	150	F		
6676-D3	Standard	0.021" (0.53mm)	180	F		
6677-71	Newton LT(13.5cm)	0.035" (0.89mm)	150	F	H	
6680-11	Super Stiff	0.035" (0.89mm)	150	F		
6680-23	Super Stiff	0.035" (0.89mm)	260	F		5
6680-31	Super Stiff	0.038" (0.97mm)	150	F		
6680-51	Super Stiff	0.035" (0.89mm)	100	F		
6680-61	Super Stiff	0.035" (0.89mm)	80	F		
6680-71	Super Stiff	0.035" (0.89mm)	180	F		
6690-41	Moveable Core	0.035" (0.89mm)	150	M		
IQ35F80B	Bentson	0.035" (0.89mm)	80	F		
IQ35F150B	Bentson	0.035" (0.89mm)	150	F		
IQ35F150BC	Bentson C	0.035" (0.89mm)	150	F		
IQ35F150BST	Bentson Short Taper	0.035" (0.89mm)	150	F		
IQ35F150LLLLT	Newton LLLT (23.5cm)	0.035" (0.89mm)	150	F		
IQ35F150LLLT	Newton LLT (18.5cm)	0.035" (0.89mm)	150	F		
IQ35F150NLT	Newton LT (13.5cm)	0.035" (0.89mm)	150	F		
IQ35F150S	Standard	0.035" (0.89mm)	150	F		10
IQ35F180B	Bentson	0.035" (0.89mm)	180	F		
IQ35F180BC	Bentson C	0.035" (0.89mm)	180	F		
IQ35F180BST	Bentson Short Taper	0.035" (0.89mm)	180	F		
IQ35F260B	Bentson Exchange	0.035" (0.89mm)	260	F		
IQ35F260S	Standard Exchange	0.035" (0.89mm)	260	F		
IQ38F150B	Bentson	0.038" (0.97mm)	150	F		
IQ38F150BC	Bentson C	0.038" (0.97mm)	150	F		
IQ38F150S	Standard	0.038" (0.97mm)	150	F		
IQ38F260S	Standard Exchange	0.038" (0.97mm)	260	F		
IQH35F150B	Bentson	0.035" (0.89mm)	150	F	H	
IQH35F150NLT	Newton LT (13.5cm)	0.035" (0.89mm)	150	F	H	
IQH35F150S	Standard	0.035" (0.89mm)	150	F	H	
IQH35F180B	Bentson	0.035" (0.89mm)	180	F	H	5
IQH35F180BST	Bentson Short Taper	0.035" (0.89mm)	180	F	H	
IQH38F150B	Bentson	0.038" (0.97mm)	150	F	H	
IQR35F150B	Bentson	0.035" (0.89mm)	150	F		
IQR35F150BST	Bentson Short Taper	0.035" (0.89mm)	150	F		